



LOGON SYSTEMS



LS WINDOWS TOUCH POS SYSTEM

Model : LS-1508I

SYSTEM CONFIGURATION

Processor	Intel CORE I3 - 10110 CPU / 2.5 GHz
System Memory	Factory Default 04 Gb Ram
Chipset	Intel® NM70 Express Chipset
Display Graphics	Intel® HD Graphics 500
Storage Device	1 * MSATA slot supports SSD / WIFI, SSD transfer speeds of up to 6Gbps, Storage features 1 * SATAII hard disk interface, transfer rate up to 3Gbps , Factory default 128Gb SSD
Power Supply	12V / 60W
OS support	WIN10 / WIN11 / Linux / POSReady 7 / POSReady 2009
RAM/Memory	08 gb

DISPLAY & TOUCH

LCD Display	15.6" TFT LED (326mm * 252 mm) , Bezel free Flat Multi touch capacitive touch screen.
LCD Resolution	1366 x 768
Touch Function	PNP Capacitive Touch
Response Time	16 ms
Appearance	Rugged Metal frame , Sleek Model.

I/O & EXPANSION

Serial Port	2 com ports
Standard USB Port	5
LAN Port	10 / 100 / 1000 Mb
VGA Port	1 * VGA1 interface with DB15 same signal 2 * 5pin
HDMI Port	Yes
Audio	1 * Audio I / O interface (microphone and line-out)

PHYSICAL DIMENSIONS

Weight (N. W. in kg)	8.5 kg
Dimension (W x D x H in mm)	335 x 210 x 340

ENVIRONMENTAL

Storage Condition	-30°C - 70°C, 10%RH - 90%RH
Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)

** The product information and specifications are subject to change without prior notice.

