



**LOGON
SYSTEMS**



LS Bluetooth Thermal Receipt Printer

Model : LP - 303

SPECIFICATION

Printing method	Direct thermal
Column capacity	576dots/line OR 512dots/line
Character size	ANK, FontA: 1.5x30.mm (12x24dots)
Font B	1.1x2.1mm (9x17dots)
Simplified/traditional	24x24dot
Printing speed	260mm/s
Receive buffer	128k bytes
NV flash buffer	256K bytes
Paper width	79.5±0.5mm
MCBF(life)	125km
Dimension	200×145×137mm
Gross weight	2.5kg
Auto cutter	whole or partial (option)
Paper end sensor	Yes
Roll paper	79.5±0.5mm* f83mm
Cash drawer control	DC 24V/1A
Power adapter	input AC 110V/220V, 50~60Hz; output: DC 24V/2.5A
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7
Bar code environment	JUPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8) / Storage CODABAR/ITF/CODE39/CODE93/CODE128
Storage environment	temperature (-10~60℃) humidity (10~90%)
Working environment	temperature (0~45 °c) humidity (10~80%)
Sensor	Cover open, Receipt coming, Error alarm
Command	Compatible with ESC/POS
Print Support	Raster &/or ASCII text
Interface	USB + Bluetooth

