



**LOGON  
SYSTEMS**



## LS WI-FI THERMAL RECEIPT PRINTER

**Model : LP - 306**

### SPECIFICATION

|                        |                                                                                       |
|------------------------|---------------------------------------------------------------------------------------|
| Printing method        | Direct thermal                                                                        |
| Column capacity        | 576dots/line v OR 512dots/line                                                        |
| Character size         | ANK, FontA: 1.5x30.mm (12x24dots)                                                     |
| Font B                 | 1.1x2.1mm (9x17dots)                                                                  |
| Simplified/traditional | 24x24dot                                                                              |
| Printing speed         | 260mm/s                                                                               |
| Receive buffer         | 128k bytes                                                                            |
| NV flash buffer        | 256K bytes                                                                            |
| Paper width            | 79.5±0.5mm                                                                            |
| MCBF(life)             | 125 km                                                                                |
| Dimension              | 200×145×137mm                                                                         |
| Gross weight           | 2.5kg                                                                                 |
| Auto cutter            | whole or partial (option)                                                             |
| Paper end sensor       | Yes                                                                                   |
| Paper thickness        | 0.06-0.08mm                                                                           |
| Roll paper             | 79.5±0.5mm* f83mm                                                                     |
| Cash drawer control    | DC 24V/1A                                                                             |
| Power supply           | DC24V/2.5A                                                                            |
| Power adapter          | input AC 110V/220V, 50~60Hz; output: DC 24V/2.5A                                      |
| Drivers                | Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7                         |
| Bar code environment   | JUPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8) / Storage<br>CODABAR/ITF/CODE39/CODE93/CODE128 |
| Storage environment    | temperature (-10~60°c) humidity (10~90%)                                              |
| Working environment    | temperature (0~45 °c) humidity (10~80%)                                               |
| Sensor                 | Cover open, Receipt coming, Error alarm                                               |
| Command                | Compatible with ESC/POS                                                               |
| Print Support          | Raster &/or ASCII text                                                                |
| Interface              | USB + LAN                                                                             |

