



**LOGON
SYSTEMS**



LS LABEL PRINTER

Model : LS - B910



PRINTING FEATURES

Resolution	203 DPI
Print Method	Direct Thermal
Max. print speed	152 mm(6")/s Max.
Max. print width	108 mm (4.25")
Max. print length	1778 mm (70")

MEDIA

Media types	Continuous, gap , blackmark, fan-fold and punched hole
Media width	32 ~ 118 (1.0"- 4.6")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")
Label length	10 ~ 1778 mm (0.39" ~ 70")
Label roll capacity	110 mm (5") (External diameter)



LOGON SYSTEMS



LS LABEL PRINTER

Model : LS - B910

PERFORMANCE FEATURES

Processor	32-bit CPU
Memory	8MB Flash Memory/8MB SDRAM
Interface	Standard:USB

FONTS/GRAPHICS/SYMBOLOLOGIES

Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN - 8, EAN-13, EAN-128, UPC-A, UPC-A, EAN and UPC 2(5) digits add-on, MSI, PLESSY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, CPCL

PHYSICAL FEATURES

Dimensions	265(D)*175(W)*172(H)
Weight	1.46 Kg

RELIABILITY

Warranty	12 months
Print head life	50 km

SOFTWARE

Driver	Windows/Linux/Mac
SDK	Windows/Android/iOS

SOFTWARE

Input	AC 100-240V, 50 -60Hz
Output	DC 24V, 2.5A, 60W

OPTIONS

Factory Options	1. USB 2. USB+Lan+Serial 3. USB+Bluetooth 4. USB+WIFI
------------------------	---

ENVIRONMENTAL PARAMETERS

Operation environment	5 ~ 40°C (41~104°F), Humidity 25 - 85% non-conditioning
Storage environment	~40 ~ 60°C (~40~140°F), Humidity:10 ~ 90% non-condensing